

# Dualys<sup>3</sup>

The dual-sided color printer for plastic card personalization



Color &  
Monochrome  
Thermal  
Transfer



300 dpi



Dual-sided



29 s/card



0.25 - 1 mm  
(10 - 40 mil)



3 years

**evolIS**

[www.evolis.com](http://www.evolis.com)

From bulk personalization of cards to individual card printing, **Dualys<sup>3</sup>** is the one-stop color printer for dual-sided personalization of badges, sterling quality and robust security.

Thanks to the most advanced printing engine in the market, **Dualys<sup>3</sup>** prints high-definition badges within seconds. This solution benefits from the latest encoding technologies: ISO or JIS2 magnetic tracks, and smart card with contact or contactless (RFID). These encoding options can be combined to personalize multifeatured cards in a single pass, paving the way to a wide range of market applications in various industries: identification, biometric security, transport, financial institutions, educational organizations, loyalty programs, and leisure.

**Dualys<sup>3</sup>** comes with a detachable 100-card feeder. Yet, you can also use it as a compact badge or card counter, thanks to a manual feed option that prints your badges one by one.

Because the Evolis products have earned market-proven reliability, Evolis is committed even further to superior quality and introduces a **3-year warranty** on the full **Dualys<sup>3</sup>** range of printers.

### GENERAL SPECIFICATIONS

- Color printing module
- 300 dpi print head (11.8 dots/mm)
- USB connection
- Option for Ethernet TCP-IP connection
- 16 MB RAM allowing two card storages (front & back)
- Flip-over station for dual-sided printing
- Detachable feeder with a capacity of 100 cards (0.76 mm - 30 mil)
- Output hopper with a capacity of 100 cards (0.76 mm - 30 mil)
- 1-Button and 4-LED control panel

### PRINT MODES

- Color dye sublimation and monochrome thermal transfer
- Enhanced color management system for top quality pictures
- Edge-to-edge printing
- Dual-sided printing
- Integrated ribbon saver for monochrome printing

### PRINTING SPEED

Personalization throughput will depend on card design and printer settings

- Color 1 side (YMCKO): 150 cards/hour
- Color 2 sides (YMCKO-K): 125 cards/hour
- Monochrome 1 side: up to 1000 cards/hour<sup>1</sup>
- Monochrome 2 sides: up to 350 cards/hour<sup>1</sup>

### SUPPORTED PLATFORMS

- Windows™ XP, 2003 and Vista, 32 & 64 bits
- Mac™ OS X v10.2, 10.3 and 10.4
- Linux

### SOFTWARE SUPPLIED

- eMedia Card Designer Software for designing and editing badges
- Compatible with Windows™ XP, 2003 and Vista
- Connection to Microsoft™ Excel databases

### RIBBON TYPES

- 2-panel KO black monochrome ribbon - 500 cards/roll
- 5-panel YMCKO color ribbon - 200 cards/roll
- 6-panel YMCKO-K color ribbon - 200 cards/roll
- Half-panel YMCKO color ribbon - 400 cards/roll
- Monochrome ribbons - up to 1000 cards/roll (black, red, green, blue, white, gold and silver)
- Special ribbons:
  - Varnish hologram - 350 cards/roll
  - Scratch-Off - up to 1000 cards/roll

### OPTIONS

- Encoding options (can be combined):
  - Magnetic stripe encoder ISO 7811 HiCo/LoCo or JIS2
  - Smart contact station - ISO 7816-2
  - Smart contact station and encoding unit - PC/SC, EMV 2000-1
  - Contactless encoding unit - ISO 14443A, B, ISO 15693, Mifare, DesFire, HID iCLASS
  - Other types upon request
- 100-card additional feeder
- Manual card feeder
- Travel bag
- Cleaning kits

### WARRANTY

Use Evolis Genuine products for best performance and extended lifespan of your printer

- Printer, print head: 3-year warranty, unlimited number of passes<sup>2</sup>



#### Card types

#### Card format

#### Card thickness

#### Card feeder capacity

#### Card output hopper capacity

#### Printer size

#### Printer weight

#### Connections

#### Electrical

#### Environmental

- All PVC, Composite PVC cards, PET, ABS<sup>1</sup> and special varnished<sup>1</sup> cards
- ISO CR-80 - ISO 7810 (53.98 mm x 85.60 mm - 3.375" x 2.125")
- From 0.25 mm (10 mil) to 1 mm (40 mil) - Dual-sided printing recommended from 0.50 mm (20 mil)
- 100 cards (0.76 mm - 30 mil), 300 cards (0.25 mm - 10 mil)
- 100 cards (0.76 mm - 30 mil), 300 cards (0.25 mm - 10 mil)
- Height: 235 mm (9.25") - Length: 447 mm (17.59") - Width: 237 mm (9.33")
- 7.4 Kg (16.31 Lbs)
- USB (cable supplied) - Option for Ethernet TCP-IP
- Power supply: 110-230 Volts AC, 1.8 A, 60-50 Hertz  
Printer: 24 Volts DC, 3 A
- Min/max operating temperature: 15° / 30° C (59° / 86° F)  
Humidity: 20% to 65% non-condensing  
Min/max storage temperature: -5° / +70° C (23° / 158° F)  
Storage humidity: 20% to 70% non-condensing  
Operating ventilation: free air



1. Under specific conditions.

2. Subject to observance of specific conditions and use of Evolis genuine consumables.



#### EUROPE, MIDDLE EAST, AFRICA

##### Evolis Card Printer

29, Avenue de la Fontaine - Z.I. Angers-Beaucouzé  
49070 Beaucouzé - France  
Tel: +33 (0) 241 367 606 - Fax: +33 (0) 241 367 612  
info@evolis.com

#### AMERICAS

##### Evolis Inc.

1835 South Perimeter Road - Suite 190  
Fort Lauderdale - FL 33309 - USA  
Tel: (954) 491-9898 - Fax: (954) 491-5140  
evolisinc@evolis.com

#### ASIA PACIFIC

##### Evolis Asia Pte Ltd

Centennial Tower, Level 21 - 3 Temasek Avenue  
Singapore 039190  
Tel: +65 6549 7606 - Fax : +65 6549 7001  
evolisasia@evolis.com